

Product Information **051XYP 051XP**

Product structure		
Backing	Heavy XY- or X-	X-weight polyester cloth
Flexibility	low 1	5 10 15 extremly high
Grain Type	Ceramic + alum	minium oxide
Coating	Closed	05120 40 mmore and 05120 40 mmore
Top Coat	stearate	Special top coat
Manufactured Width	1400 mm	
Form	∞ •	
Suitable for	hand grinding	g hand held machine grinding machine grinding
Grits		Ceramic, zirconia, # and * = non P-Grits
☐ P 12 ☐ P 16 🔀 24 [P 30 🔀 36 🔀 40	P 50 ∑ 80 100 ∑ 120 P 150 P 180 P 220 P 240
P 280 P 320 P 360	P 400 P 500 P 600	0 P 800 P 1.000 P 1.200 P 1.500 P 2.000 P 2.500 ST 3.000 ST 6.000 ST 8.000
Materials		
Aluminium Non-ferrous metal	Stainless steel	Titanium Paint Glass Wood Plastics Stone/china

Application examples



Coil | Removing black scale and mill scale



Wire | Removing black scale



Implants & medical devices | Green body deburring

- Highest stock removal due to ceramic abrasive grain and special top coat
- Very long service life and cool grinding effect due to special grinding additives and self sharpening effect
- Particulary suitable for high grinding pressure because of heavy XY- and X-weight polyester cloth backing

