

## Product Information **062XP**

Produc	t structu	re												
Backing				Very heavy X-weight polyester backing										
Flexibil	ity	•••••	•••••	low	1	5	•••••	10 high		•••••				
Grain Type				•••••••••••••••••••••••••••••••••••••••									0530	36
Coating				semi open								and the same		
Top Coat				s s	stearate special top coat									
Manufactured Width				1	400mm	143	0mm	<b>⊠</b> 1650mn	n ot	hers				
Form	•••••	•••••	• • • • • • • • • • • • • • • • • • • •					•••••	• • • • • • • • • • • • • • • • • • • •	••••				
Suitable for				hand sanding And held machine sanding machine sanding										
Grits												Ceramio	c, zirconia, # a	nd * = non P-Grits
P 12	P 16	P 24	P 30	36	<b>4</b> 0	<b>&gt;</b> 50	<b>6</b> 0	80	100	120	P 150	P 180	P 220	P 240
P 280	P 320	P 360	P 400	P 500	P 600	P 800	P 1.0	00 P 1.200	P 1.500	P 2.000	P 2.500	ST 3.000	ST 6.00	00 ST 8.000
Materia	ls													
Aluminiu	m No	on-ferrous Metal	Stair ste		Steel	Titan	ium	Paint lacquer	Glass		Wood	Plastic	s :	Stone/china

## **Application examples**





Solid parquet and boards

Sanding belts | Plane and Finish sanding

Sanding discs | Pre- and Finish sanding

- High-performance ceramic abrasive grain ensures high stock removal rate
- Long service life due to an optimized semi open grain coat
- Achieving high class surfaces by precise coated abrasive grain

