

## **Product Information** 514D | 514C2

Produc	t struct	ure													
Backing				Robu	Robust D- and flexible C- weight latex paper										
Flexibil	lity	•••••	•••••	low	1	5	<b>T</b>	10 high	• • • • • • • • • • • •	• • • • •					
Grain Type					Aluminium oxide										
Coating				very	very open										
Top Coat				St.	stearate special top coat										
Manufactured Width					400mm	143	30mm <b>2</b>	<b>▼</b> 1650mm	n 🔲 o	thers					
Form				5				$\odot$	<b>Q</b> , [						
Suitable for				<b>⊠</b> h	hand sanding hand held machine sanding machine sanding										
Grits												Cerami	c, zirconia, # :	and * = non P-Grits	
P 12	P 16	P 24	P 30	P 36	<b>№</b> P 40	P 50	<b>№</b> P 60	<b>№</b> P 80	P 100	<b>№</b> P 120	P 150	<b>№</b> P 180	<b>№</b> P 220	P 240	
<b>∑</b> P 280	P 320	0 X P 360	P 400	<b>№</b> P 500	<b>∑</b> P 600	<b>№</b> P 800	P 1.000	P 1.200	P 1.500	P 2.000	P 2.500	ST 3.000	ST 6.0	00 ST 8.000	
Materia	als														
Aluminiu	ı mı	Non-ferrous Metal	Stair ste		Steel	Titan	iium	Paint lacquer	Glas	S	Wood	Plastic	S	Stone/china	
Applica	Application examples														
	No.		4		The state of the s							3000	122-		







Furniture industry

Wind generator industry

- Smooth latex paper backing for optimal flexibility to a suit plain and contoured surfaces
- Increased sanding time due to an optimized abrasive grain coating in combination with a special anti-clogging system

